

# FSPDB SERIES: POWER DISTRIBUTION BLOCKS

## UL APPROVED FOR 100kA

- Mersen Finger-Safe PDBs meet 100kA Short Circuit Current Rating
  - (SCCR) per UL 1059
  - (Reference: UL File E73571)
- Preferred by electrical panel shops to meet latest requirements of NEC and UL508a
  - SCCR Rated
  - Touch Safe
  - Wide Product Offering
  - Availability



Catalog Number	Amps	SCCR	Wire Range		Required Overcurrent Protection					
			Line	Load	Class J [AJT, A4J, HSJ]	Class T [A3T/A6T]	RK1 [A2D/A6D, A2K/A6K, HSRK]	RK5 [TR/TRS]	Class G [AG]	Class CC [ATDR, ATQR, ATMR]
FSPDB1A	175	100kA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB1C	175	100kA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB2A	175	100kA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB2C	175	100kA	2/0-#14	2/0-#14	200A	200A	200A	100A	60A	30A
FSPDB3A	310	100kA	350-#6 & 2/0-#14	2/0-#14	400A	400A	400A	200A	60A	30A
FSPDB3C	310	100kA	350-#6 & 2/0-#14	2/0-#14	400A	400A	400A	200A	60A	30A