Class J Fuse Holders - Gen2

Fuse Bases

FUSE BASES, FUSE HOLDERS, FUSE SYSTEMS



Mersen's new Generation 2 open style class J fuse blocks accommodate class J fuses ranging from 0-100A, 600V. A choice of screw, pressure plate, and box connectors fit a wide range of stranded or solid wire. Gen2 fuse blocks are DIN-rail mountable, more compact than the traditional offering, and feature dovetail nesting for multipole field assembly. Fuse bases are IP20 rated when paired with Mersen's newly designed dead front covers.

Technical Data Overview			
Volts	600VAC/DC		
Amps	30A, 60A, 100A		
Short-Circuit Current Rating (SCCR)	200kA		
Recommended fuse usage	AJT, A4J, HSJ		

FEATURES/BENEFITS

- DIN-rail mountable, 600V, 30-100A fuse bases
- Mersen Certified 700VAC
- 30A is available with box, screw, and pressure plate terminations; 60A & 100A is available with box only
- Fresh new Mersen gray color for fuse base
- Dovetail design for interlocking configuration of 2-pole and 3-pole bases
- Unique molding around the termination to accommodate hinged cover and for increased safety
- Built-in lockout/tagout feature
- IP20 finger safe
- New clear covers with indicators for safety and visual inspections
- Multi-connector wiring options

APPLICATIONS

- Branch circuits
- Control panels
- Load centers
- Lighting, heating, & general loads

APPROVALS/STANDARDS

- All class J fuse blocks meet the requirements of UL4248 (formerly UL512)
- UL listed Guide IZLT, File E52283
- CSA certified class 6225, File 32169





CATALOG NUMBERS

600 Volt, 30, 60, & 100 Ampere Class J Fuse Blocks


Ampere Rating Pol	Poles	Connectors	nnectors	Catalog Number Description	Connector Torrero In . Ib	F:	
	Foles	Types	Wire Range		Description	Connector Torque In - Ib	Figure
:	1	BOX 2-14 AWG	FB60J30B1	Fuse base 600V J 30A Box 1-P			
	2		2-14 AWG CU-AL	FB60J30B2	Fuse base 600V J 30A Box 2-P	4.0 N-m (35 in-lbs) CU-AL	1
	3			FB60J30B3	Fuse base 600V J 30A Box 3-P		
	1			FB60J30S1	Fuse base 600V J 30A Screw 1-P		
30	3 CU or 3 PRESSURE 10-14	V 10-14 AWG CU only	FB60J30S2	Fuse base 600V J 30A Screw 2-P	2.3 N-m (10 in-lbs) CU wire	2	
			coonig	FB60J30S3	Fuse base 600V J 30A Screw 3-P		
			FB60J30P1	Fuse base 600V J 30A PP 1-P	2.3 N-m (10 in-lbs) CU wire		
		PRESSURE 10-14 AWG PLATE CU only	FB60J30P2	Fuse base 600V J 30A PP 2-P		3	
	3			FB60J30P3	Fuse base 600V J 30A PP 3-P		
	1		FB60J60B1	Fuse base 600V J 60A Box 1-P	5.1 N-m (45 in-lbs) CU-AL		
60 2 B0	BOX	2-14 AWG CU-AL	FB60J60B2	Fuse base 600V J 60A Box 2-P		4	
			FB60J60B3	Fuse base 600V J 60A Box 3-P			
100	1		OX 2/0-6 AWG	FB60J100B1	Fuse base 600V J 100A Box 1-P		
	2	BOX		FB60J100B2	Fuse base 600V J 100A Box 2-P	11.3 N-m (100 in-lbs) AL wire; 6.8 N-m (60 in-lbs) CU wire	5
	3		FB60J100B3	Fuse base 600V J 100A Box 3-P	_ =====================================		

Dead Front Covers for 600 Volt Class J Fuse Blocks

Ampere Rating	Catalog Number	Description	Figure	
20	FBC60J30	Cover 600V J 30A W/O IND	6	
30	FBC60J30I	Cover 600V J 30A W/IND	6	
60	FBC60J60	Cover 600V J 60A W/O IND		
FBC60J60I		Cover 600V J 60A W/IND		
400	FBC60J100			
100	FBC60J100I	Cover 600V J 100A W/IND	8	


DIMENSIONS

Figure 1: Class J 30A - Box Connector




Catalog Number	No. of Poles	"A" Dimension
FB60J30B1	1	1.18"
FB60J30B2	2	2.36"
FB60J30B3	3	3.54"

Figure 2: Class J 30A - Screw




Catalog Number	No. of Poles	"A" Dimension
FB60J30S1	1	1.18"
FB60J30S2	2	2.36"
FB60J30S3	3	3.54"

Figure 3: Class J 30A - Pressure Plate




Catalog Number	No. of Poles	"A" Dimension
FB60J60P1	1	1.18"
FB60J60P2	2	2.36"
FB60J60P3	3	3.54"


Figure 6: Class J Cover 30A



DIMENSIONS:


Figure 4: Class J 60A - Box Connector






Catalog Number	No. of Poles	"A" Dimension
FB60J60B1	1	1.5"
FB60J60B2	2	3.0"
FB60J60B3	3	4.5"

Figure 5: Class J 100A - Box Connector





Catalog Number	No. of Poles	"A" Dimension
FB60J100B1	1	1.9"
FB60J100B2	2	3.8"
FB60J100B3	3	5.7"

Figure 7: Class J Cover 60A




Figure 8: Class J Cover 100A

